Permabond 792

Revision nr.3 Dated 17/02/2025

Printed on 16/06/2025
Page n. 1 / 10
Replaced revision:2 (Dated 16/12/2024)

ΕN

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Permabond 792 Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Industrial **Identified Uses Professional** Consumer Use

1.3. Details of the supplier of the safety data sheet

Name **Permabond Engineering Adhesives** Full address Niederkasseler Lohweg 18 District and Country 40547 Düsseldorf Germany

Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet info.europe@permabond.com

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common,

Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

+44 (0)1962 711 661 (8.00 am-5.00 pm For urgent inquiries refer to Mon-Fri)

> CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation. Specific target organ toxicity - single exposure, H335 May cause respiratory irritation. category 3

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 2 / 10 Replaced revision:2 (Dated 16/12/2024)

SECTION 2. Hazards identification

Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation. H315 Causes skin irritation. H335 May cause respiratory irritation.

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Precautionary statements:

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Contains: ethyl 2-cyanoacrylate

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0.1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. %Classification (EC) 1272/2008 (CLP)

ethyl 2-cyanoacrylate

INDEX 607-236-00-9 $60 \le x < 100$ Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, EUH202

EC 230-391-5 EUH202: ≥ 0%, STOT SE 3 H335: ≥ 10%

7085-85-0 CAS

REACH Reg. 01-2119527766-29-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

SKIN: Upon contact with the product, the skin will stick to itself and to everything else immediately. Do not attempt to remove either contaminated clothing or the product from the skin, as adherent skin can easily tear. Wash the skin thoroughly with soap and water. Consult a doctor immediately. EYES: Rinse immediately with plenty of water. Continue rinsing for at least 10 minutes. In the event of sticking with adhesive, do not force the eyelids apart. Apply a swab soaked in warm water and allow the eyelids to separate. Consult a doctor. The solidified adhesive does not stick to the surfaces of the eyes but being abrasive can cause damage. Consult a doctor immediately. INGESTION: Upon contact, the product can immediately stick the lips together. Do not induce vomiting. Consult a doctor. INHALATION: Ventilate the area. Move the subject to fresh air, away from the scene of the accident. If you feel unwell, consult a doctor.

Rescuer protection

Information not available

4.2. Most important symptoms and effects, both acute and delayed

INHALATION: Irritation of nose, throat and airways. INGESTION: Upon contact, the product may immediately stick lips together. SKIN: Prolonged contact with skin may cause redness and irritation. EYES: Irritating and may cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to the DOCTOR: In case of STUCK SKIN. Slowly separate the skin starting from the edge of the stuck area. Use warm soapy water. In case of STUCK EYES. DO NOT force the eyelids open. Apply a warm water compress and allow the eyes to reopen on their own.



Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 3 / 10 Replaced revision:2 (Dated 16/12/2024)

SECTION 4. First aid measures .../>>

Means to have available in the workplace for specific and immediate treatment

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Adhesive



Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025
Page n. 4 / 10
Replaced revision:2 (Dated 16/12/2024)

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DNK Danmark BEK nr 291 af 19/03/2024 (Historisk) Bekendtgørelse om grænseværdier for stoffer og materialer

(kemiske agenser) i arbejdsmiljøet

ESP Límites de exposición profesional para agentes químicos en España 2024 **Fspaña** Suomi HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH FIN

HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25

ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 POL Polska

czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i

local

systemic

local

systemic

natężeń czynników szkodliwych dla zdrowia w środowisku pracy

Sverige Arbetsmiljöverkets föreskrifter och allmänna råd (AFS 2023:14) om gränsvärden för

luftvägsexponering i arbetsmiljön

ethyl 2-cyanoacrylate														
Threshold Limit Value														
Туре	Country	TWA/8h		STEL/15min			Remarks / Observations							
	-	mg/m3	ppm	m	g/m3	ppm								
TLV	DNK	10	2	2	20	4								
VLA	ESP		0,2											
HTP	FIN	1	0,2											
NDS/NDSCh	POL	1			2									
NGV/KGV	SWE	10	2	2	20	4								
Health - Derived no-effect level - DNEL / DMEL														
Effects on consumers														
Route of exposure Ac		cute Acute	Э	Chronic	Chronic	Acute	Acute	e Chronic	Chronic					

systemic

9.25

mg/m3

Inhalation

SWE

Legend: (C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

local

9.25

mg/m3

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

local

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

systemic

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 5/10 Replaced revision:2 (Dated 16/12/2024)

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance		Value liquid		Information		
Colour		colourless				
Odour		pungent				
Melting point / freezing point		not applicable				
Initial boiling point	>	100	°C			
Flammability		not available				
Lower explosive limit		not available				
Upper explosive limit		not available				
Flash point		83	°C			
Auto-ignition temperature		not available				
Decomposition temperature		not available				
рН		not available		Reason for missing on non-soluble	data:substan (in	ce/mixture is water)
Kinematic viscosity		not available				
Dynamic viscosity		~ 95 mPa.s		Temperature: 23 °C		
Solubility		not available				
Partition coefficient: n-octanol/water		not available				
Vapour pressure		0,6	mBar	Temperature: 25 °C		
Density and/or relative density		1,1				
Relative vapour density		not available				
Particle characteristics		not applicable				

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

The product can react with water generating heat.

10.2. Chemical stability

Stable to normal environment temperatures if used as recommended.

10.3. Possibility of hazardous reactions

The reactions with the following materials can generate heat: alcohol water. Alkali. Amine.

10.4. Conditions to avoid

Do not add water directly to the product. It may cause a violent reaction.

10.5. Incompatible materials

Water, alcohol, amine.

10.6. Hazardous decomposition products

Heating can generate the following products: Gas/Vapors/Toxic fumes of: Dioxide of carbon (CO2). Carbon monoxide (CO). Nitrosis gas (NOX). Hydrogen cyanide (HCN).



Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 6 / 10 Replaced revision:2 (Dated 16/12/2024)

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Cyanacrililated are not classified as sensitizing according to European legislation and the their rapid polymerization in contact with humidity makes the occurrence of similar unlikely Phenomena, however, ACGIH, American Conference of Governmental Industrial Hygienists, It reports some sporadic cases of awareness of the skin and respiratory system.

It can cause allergic reactions in predisposed subjects.

Information on likely routes of exposure

Inhalation: irritating to the respiratory tract.

Ingestion: in contact the product can immediately glue the lips together.

Contact with the skin: irritating for the skin. Contact with the product, the skin will stick to itself and to any

Another thing immediately.

Contact with eyes: irritating for the eyes. In contact, the product makes the eyelids join together. His vapors are

tear gas.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

ethyl 2-cyanoacrylate LD50 (Dermal): LD50 (Oral):

> 2000 mg/kg > 5000 mg/kg

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class



Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 7 / 10 Replaced revision:2 (Dated 16/12/2024)

SECTION 11. Toxicological information/>>

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Not considered dangerous for the environment.

The mixture is classified on the basis of dangerous information for the ingredients such as defined by the classification criteria for mixtures for each danger class or according to differentiations present in Annex I of 1272/2008/EC. The available information of health/ecological relevant for substances are indicated in section 3 below.

12.2. Persistence and degradability

Information not available

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

ΕN



Permabond Engineering Adhesives

Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 8 / 10 Replaced revision:2 (Dated 16/12/2024)

SECTION 13. Disposal considerations .../>>

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: UN 3334

It applies only to internal containers> 500ml.

14.2. UN proper shipping name

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: AVIATION REGULATED LIQUID, N.O.S. (ethyl 2-cyanoacrylate)

14.3. Transport hazard class(es)

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: II

14.5. Environmental hazards

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: - Limited Quantities: - Tunnel restriction code: -

Special provision: -

IMDG: EMS: - Limited Quantities: -

IATA: Cargo: Maximum quantity: 450 L Packaging instructions: 964

Passengers: Maximum quantity: 450 L Packaging instructions: 964

Special provision: A27

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

3

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point

Contained substance

Point 75

EPY 11.9.0 - SDS 1004.14

ΕN



Permabond Engineering Adhesives

Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 9 / 10 Replaced revision:2 (Dated 16/12/2024)

SECTION 15. Regulatory information .../>>

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

H319 Causes serious eye irritation.H315 Causes skin irritation.

H335 May cause respiratory irritation.

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.



Permabond 792

Revision nr.3 Dated 17/02/2025 Printed on 16/06/2025 Page n. 10 / 10 Replaced revision:2 (Dated 16/12/2024)

SECTION 16. Other information .../>>

- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- 27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

13.